

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)


(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
11 December 2003 (11.12.2003)

PCT

(10) International Publication Number
WO 03/102553 A1

- (51) International Patent Classification⁷: **G01N 21/03**, 21/35, 21/61
- (21) International Application Number: PCT/GB03/02341
- (22) International Filing Date: 29 May 2003 (29.05.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0212631.6 31 May 2002 (31.05.2002) GB
- (71) Applicant (for all designated States except US): **E2V TECHNOLOGIES LIMITED** [GB/GB]; 106 Waterhouse Lane, Chelmsford, Essex CM1 2QU (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **HOPKINS, Graham, P.** [GB/GB]; c/o E2V Technologies Limited, 106 Waterhouse Lane, Chelmsford, Essex CM1 2QU (GB). **HAYWARD, A., S.** [GB/GB]; c/o E2V Technologies Limited, 106 Waterhouse Lane, Chelmsford, Essex CM1 2QU (GB).
- (74) Agent: **LOVELESS, Ian, Mark**; Reddie & Grose, 16 Theobalds Road, London WC1X 8PL (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
- with international search report
 - before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: GAS SENSORS

(57) Abstract: A gas sensor of the type having a housing defining a chamber within which light is transmitted from a source to a detector through an optical path, includes internal mirror portions having part ellipsoidal shape. Light is transmitted from a source to a detector via the reflective portions. The detector is arranged to sense light only from a limited range of angles, such that only light transmitted through a defined optical path reflected off the two reflective portions from the source reaches the sensor. This ensures that there is a constant optical path from the source to the detector, which improves the signal to noise ratio of the device.